

T420 Print Cartridge

Printer: T420

Declaration of Yield:

Average Cartridge Yield 5000 standard pages Declared yield value in accordance with ISO/IEC 19752
--

Average 6428
Std Dev 328
90% Lower
Confidence 6258

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start stop
21-Nov-2004 23-Nov-2004

Number of cartridges in testing	12	
Qty. of cartridges used in calculation	12	
Shake Procedure	1st shake	At toner low
	2nd shake	At toner low
Print mode		Continuous
Number of printers tested		4
Media used		Boise Cascade X-9 - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		8.01
Operating system		Windows 2000
Application software		Adobe Acrobat version 6.01
Test page version		IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAD041691980	89000XB	74	75	74	49	49	48	6,656	Y
CAD041700155	89000VG	74	75	74	49	49	48	6,526	Y
CAD041821493	89000WG	74	75	74	49	49	48	6,177	Y
CAD041965717	8906812	74	75	74	49	49	48	5,695	Y
CAD041965938	89000XB	74	74	74	49	49	48	6,574	Y
CAD041691975	89000VG	74	74	74	49	49	48	6,722	Y
CAD041700126	89000WG	74	74	74	49	49	48	6,557	Y
CAD041820279	8906812	74	74	74	49	49	48	6,066	Y
CAD041821716	89000XB	74	75	74	48	48	48	6,713	Y
CAD041965841	89000VG	74	75	74	48	48	48	6,177	Y
CAD041700127	89000WG	74	75	74	48	48	48	6,765	Y
CAD041691961	8906812	74	75	74	48	48	48	6,502	Y

Comments and or exceptions: